



- This Spacer is mounted on PCB by inserting into through-hole.
- Screws can be inserted both from component and from solder side.
- Taping type has adsorption seal for vacuum pick. It needs to be removed after reflow.
- Adaptive PCB Thickness....0.8t and over (other PCB thickness applicable)
- Current Capacity....
 TH-0.8-M2...20A
 TH-0.8-M2.6...20A
 TH-0.8-M3...30A
 TH-0.8-M4...40A
- Finish....Plated Sn over Ni base
- Material....Brass
- Recommended Metal Mask Thickness....150-200 μ

Tightening Torque....

TH-0.8-M2...1.5kgf-cm (14.7N-cm) and below
 TH-0.8-M2.6...3kgf-cm (29.4N-cm) and below
 TH-0.8-M3...5kgf-cm (49N-cm) and below (X-direction)
 TH-0.8-M3...3kgf-cm (29.4N-cm) and below (Y-direction)
 TH-0.8-M4...8kgf-cm (78.4N-cm) and below

High Torque Distribution Ltd, 6 & 7 Wren Court, Strathclyde Business Park, Bellshill ML4 3NQ, Scotland, UK.
Telephone: +44 (0)1698 749749 **Fax:** +44 (0)1698 749206 **Email:** sales@hightorque.biz
Web: www.hightorquefasteners.co.uk

VAT Number: GB817097808 **Company Registration Number:** SC249029

Fastener and Component Solutions

N/O	A	B	H	M	Package
TH-0.8-1.0-M2	4.0	2.5	1.0	M2	450
TH-0.8-1.5-M2	4.0	2.5	1.5	M2	450
TH-0.8-2.0-M2	4.0	2.5	2.0	M2	450
TH-0.8-2.5-M2	4.0	2.5	2.5	M2	350
TH-0.8-3.0-M2	4.0	2.5	3.0	M2	350
TH-0.8-3.5-M2	4.0	2.5	3.5	M2	350
TH-0.8-4.0-M2	4.0	2.5	4.0	M2	250
TH-0.8-4.5-M2	4.0	2.5	4.5	M2	250
TH-0.8-5.0-M2	4.0	2.5	5.0	M2	250
TH-0.8-1.0-M2.6	4.5	3.1	1.0	M2.6	450
TH-0.8-1.5-M2.6	4.5	3.1	1.5	M2.6	450
TH-0.8-2.0-M2.6	4.5	3.1	2.0	M2.6	450
TH-0.8-2.5-M2.6	4.5	3.1	2.5	M2.6	350
TH-0.8-3.0-M2.6	4.5	3.1	3.0	M2.6	350
TH-0.8-3.5-M2.6	4.5	3.1	3.5	M2.6	350
TH-0.8-4.0-M2.6	4.5	3.1	4.0	M2.6	250
TH-0.8-4.5-M2.6	4.5	3.1	4.5	M2.6	250
TH-0.8-5.0-M2.6	4.5	3.1	5.0	M2.6	250
TH-0.8-5.5-M2.6	4.5	3.1	5.5	M2.6	350
TH-0.8-6.0-M2.6	4.5	3.1	6.0	M2.6	350
TH-0.8-6.5-M2.6	4.5	3.1	6.5	M2.6	300
TH-0.8-7.0-M2.6	4.5	3.1	7.0	M2.6	300
TH-0.8-7.5-M2.6	4.5	3.1	7.5	M2.6	300
TH-0.8-8.0-M2.6	4.5	3.1	8.0	M2.6	300
TH-0.8-1.2-M3	5.0	3.5	1.2	M3	450

High Torque Distribution Ltd, 6 & 7 Wren Court, Strathclyde Business Park, Bellshill ML4 3NQ, Scotland, UK.
Telephone: +44 (0)1698 749749 **Fax:** +44 (0)1698 749206 **Email:** sales@hightorque.biz
Web: www.hightorquefasteners.co.uk

VAT Number: GB817097808 **Company Registration Number:** SC249029

Fastener and Component Solutions

TH-0.8-1.5-M3	5.0	3.5	1.5	M3	450
TH-0.8-2.0-M3	5.0	3.5	2.0	M3	450
TH-0.8-2.5-M3	5.0	3.5	2.5	M3	350
TH-0.8-3.0-M3	5.0	3.5	3.0	M3	350
TH-0.8-3.5-M3	5.0	3.5	3.5	M3	350
TH-0.8-4.0-M3	5.0	3.5	4.0	M3	250
TH-0.8-4.5-M3	5.0	3.5	4.5	M3	250
TH-0.8-5.0-M3	5.0	3.5	5.0	M3	250
TH-0.8-5.5-M3	5.0	3.5	5.5	M3	350
TH-0.8-6.0-M3	5.0	3.5	6.0	M3	350
TH-0.8-6.5-M3	5.0	3.5	6.5	M3	300
TH-0.8-7.0-M3	5.0	3.5	7.0	M3	300
TH-0.8-7.5-M3	5.0	3.5	7.5	M3	300
TH-0.8-8.0-M3	5.0	3.5	8.0	M3	300
TH-0.8-8.5-M3	5.0	3.5	8.5	M3	250
TH-0.8-9.0-M3	5.0	3.5	9.0	M3	250
TH-0.8-9.5-M3	5.0	3.5	9.5	M3	250
TH-0.8-10-M3	5.0	3.5	10	M3	250
TH-0.8-2.0-M4	7.0	5.5	2.0	M4	350
TH-0.8-2.5-M4	7.0	5.5	2.5	M4	250
TH-0.8-3.0-M4	7.0	5.5	3.0	M4	250
TH-0.8-3.5-M4	7.0	5.5	3.5	M4	200
TH-0.8-4.0-M4	7.0	5.5	4.0	M4	200
TH-0.8-4.5-M4	7.0	5.5	4.5	M4	450
TH-0.8-5.0-M4	7.0	5.5	5.0	M4	450
TH-0.8-5.5-M4	7.0	5.5	5.5	M4	300
TH-0.8-6.0-M4	7.0	5.5	6.0	M4	300

High Torque Distribution Ltd, 6 & 7 Wren Court, Strathclyde Business Park, Bellshill ML4 3NQ, Scotland, UK.
Telephone: +44 (0)1698 749749 **Fax:** +44 (0)1698 749206 **Email:** sales@hightorque.biz
Web: www.hightorquefasteners.co.uk

VAT Number: GB817097808 **Company Registration Number:** SC249029

Fastener and Component Solutions

TH-0.8-6.5-M4	7.0	5.5	6.5	M4	250
TH-0.8-7.0-M4	7.0	5.5	7.0	M4	250
TH-0.8-7.5-M4	7.0	5.5	7.5	M4	200
TH-0.8-8.0-M4	7.0	5.5	8.0	M4	200
TH-0.8-8.5-M4	7.0	5.5	8.5	M4	200
TH-0.8-9.0-M4	7.0	5.5	9.0	M4	200
TH-0.8-9.5-M4	7.0	5.5	9.5	M4	200
TH-0.8-10- M4	7.0	5.5	10	M4	200

High Torque Distribution Ltd, 6 & 7 Wren Court, Strathclyde Business Park, Bellshill ML4 3NQ, Scotland, UK.
Telephone: +44 (0)1698 749749 **Fax:** +44 (0)1698 749206 **Email:** sales@hightorque.biz
Web: www.hightorquefasteners.co.uk

VAT Number: GB817097808 **Company Registration Number:** SC249029